


AD ELEV: 169'

ARP S05 54 30 W035 14 57

D-ATIS 132.65	D-CL NIL	GNDC 121.90	TWR 118.70 122.80	APRON NIL
------------------	-------------	----------------	----------------------	--------------



CHANGES: APRON, INS, LAYOUT, RWK.

# ADC - SBNT: INFORMAÇÕES COMPLEMENTARES / COMPLEMENTARY INFORMATION


CARACTERÍSTICAS FÍSICAS / PHYSICAL CHARACTERISTICS											
PISTA RUNWAY				DIMENSÕES(m) DIMENSIONS(m)				PCN	TIPO DE SUPERFÍCIE SURFACE KIND		
RWY	BRG MAG	Tipo Type	RCD	RWY	SWY	CWY	STRIP	RWY	RWY	SWY	
a	b	c	d	e	f	g	h	i	j	k	
16L 34R	162 342	PA-1 NPA	4F 4F	2600x45	60X45 65X45		2720 X 280	37/F/A/X/T	ASPH	ASPH ASPH	
16R 34L	162 342	NPA NPA	4F 4F	1800x45			1920 X 280	40/F/A/X/T	ASPH		
12 30	120 300	NPA NPA	4E 4E	1825x45			1945 X 150	40/F/A/X/T	ASPH		

## DISTÂNCIAS DECLARADAS, AUXÍLIOS VISUAIS E COORDENADAS DAS CABECEIRAS DECLARED DISTANCES, VISUAL AIDS AND THRESHOLD COORDINATES


RWY	TORA(m)	TODA(m)	ASDA(m)	LDA(m)	AUXÍLIOS / AIDS	ALTURA GEOIDAL(m) GEOID HEIGHT(m)	COORDENADAS COORDINATES
16L 34R	2600 2600	2600 2600	2660 2665	2600 2600	PAPI	- 5,02 - 5,02	S05 54 07 W035 15 06 S05 55 12 W035 14 12
16R 34L	1800 1800	1800 1800	1800 1800	1800 1800	PAPI (3.01°)	- 5,01 - 5,01	S05 54 27 W035 15 22 S05 55 12 W035 14 46
12 30	1825 1825	1825 1825	1825 1825	1825 1825	PAPI (2.98°)	- 5,01 - 5,02	S05 54 33 W035 15 21 S05 54 42 W035 14 22

## SERVIÇO DE SALVAMENTO E CONTRAINCÊNDIO / RESCUE AND FIRE FIGHTING SERVICE: RFFS REQ - MIL 6


RWY 16L / 34R



RWY 16R / 34L



RWY 12 / 30



RMK:

1) MEHT: RWY 16L: 73FT  
RWY 16R: 55FT  
RWY 12: 48FT

2) PCN: TWY A - 85/F/A/X/T, TWY B 76/F/A/X/T, TWY C 44/F/A/X/T, TWY D 59/F/B/X/T, TWY E 12/R/A/X/T, TWY F 33/F/B/X/T, TWY G 32/F/A/X/T, TWY H 55/F/B/X/T, TWY I 55/F/B/X/T, TWY J 32/F/A/X/T, TWY K 44/F/A/X/T, TWY L 72/F/B/X/T, TWY M 80/F/B/X/T, TWY N 85/F/B/X/T, TWY O 22/R/B/X/T, TWY P 65/F/A/X/T.

CHANGES: APRON INS. LAYOUT. RMK