



CODING TABLE

IAC VOR RWY 25					BELÉM / Val de Cans – Júlio Cezar Ribeiro, INTL (SBBE)							SBBE_IAC_00Z		11 JUN 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	BEL	SURDI	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	ROMUC	AF	N/A	R	N/A	+2700	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	BEL	KEVOM	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	ROMUC	AF	N/A	L	N/A	+2700	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	BEL	ROMUC	IF	N/A	N/A	N/A	+2700	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	BEL	ANDIV	CF	242.09° Mag 221.84° True	N/A	N/A	R1380	N/A	N/A	4.90	N/A	FAF	N/A
30	FINAL	N/A	BEL	BE099*	CF	242.09° Mag 221.84° True	N/A	N/A	R835	N/A	N/A	1.71	-3.00	SDF	N/A
40	FINAL	N/A	BEL	BE098*	CF	242.09° Mag 221.84° True	N/A	N/A	@102	N/A	N/A	2.30	-3.00	FTP	N/A
10	MA	N/A	BEL	N/A	CA	242.09° Mag 221.83° True	N/A	N/A	+1200	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VD	300.00° Mag 279.75° True	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	MA	N/A	BEL	SURDI	AF	N/A	R	N/A	+3000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	BEL	SURDI	HM	141.86° Mag 121.61° True	L	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
KEVOM	S 01:28:14.19W 48:20:09.26
SURDI	S 01:17:47.60W 48:37:13.01
ROMUC	S 01:15:34.45W 48:22:03.25
ANDIV	S 01:19:14.64W 48:25:19.09
BE099	S 01:20:31.55W 48:26:27.51
BE098	S 01:22:14.88W 48:27:59.41

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT