



CODING TABLE

IAC ILS W RWY 07					BELÉM / Val de Cans – Júlio Cezar Ribeiro, INTL (SBBE)							SBBE_IAC_02I		10 JUL 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role Of TheFix	Navigation Specification
10	APCH	N/A	N/A	BE393	IF	N/A	N/A	N/A	+4500	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	BE367	TF	355.71° Mag / 335.43° True	N/A	N/A	+2700	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	BE392	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	BE367	TF	135.69° Mag / 115.44° True	N/A	N/A	+2700	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	BE389	IF	N/A	N/A	N/A	+4500	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	BE367	TF	65.45° Mag / 45.18° True	N/A	N/A	+2700	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	BE367	IF	N/A	N/A	N/A	+2700	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	IBE	OPRIV	CF	65.68° Mag / 45.42° True	N/A	N/A	R1690	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	IBE	BE035*	CF	65.60° Mag / 45.35° True	N/A	N/A	@93	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	CA	65.60° Mag / 45.35° True	N/A	N/A	+1200	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	MA	Y	N/A	BE172	DF	N/A	L	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	RNAV 1 or RNP 1
30	MA	Y	N/A	BE172	HM	357.10° Mag / 336.89° True	L	N/A	+4000	N/A	N/A	1.00min	N/A	MAHF	RNAV 1 or RNP 1

*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BE393	S 01:35:47.40W 48:33:44.40
BE367	S 01:30:18.60W 48:36:13.80
BE392	S 01:27:43.20W 48:41:38.40
BE389	S 01:34:33.60W 48:40:28.80
OPRIV	S 01:26:48.36W 48:32:39.50
BE035	S 01:23:16.86W 48:29:06.03
BE172	S 01:08:20.73W 48:24:58.93

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT