



CODING TABLE

SID RNAV UTPAS 6B RWY 29R					BRASÍLIA / Pres. Juscelino Kubitschek, INTL (SBBR)							SBBR_SID_02Y		29 OCT 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	RWY	N	N/A	DIBUB	CF	288.35° Mag 266.20° True	N/A	N/A	N/A	N/A	N/A	8.35	N/A	OTHER	RNAV 1 or RNP 1
20	RWY	Y	N/A	UTPAS	TF	43.03° Mag 20.93° True	R	-9000	N/A	N/A	N/A	12.80	N/A	OTHER	RNAV 1 or RNP 1
10	EPDEP	N/A	N/A	UTPAS	IF	N/A	N/A	-9000	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	EPDEP	N	N/A	EPDEP	TF	69.28° Mag 47.15° True	N/A	N/A	N/A	N/A	N/A	78.24	N/A	OTHER	RNAV 1 or RNP 1
10	ILKUS	N/A	N/A	UTPAS	IF	N/A	N/A	-9000	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	ILKUS	N	N/A	ILKUS	TF	7.15° Mag 345.02° True	N/A	N/A	N/A	N/A	N/A	46.36	N/A	OTHER	RNAV 1 or RNP 1
10	PULUV	N/A	N/A	UTPAS	IF	N/A	N/A	-9000	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	PULUV	N	N/A	PULUV	TF	39.84° Mag 17.72° True	N/A	N/A	N/A	N/A	N/A	64.10	N/A	OTHER	RNAV 1 or RNP 1
10	UGTAK	N/A	N/A	UTPAS	IF	N/A	N/A	-9000	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	UGTAK	N	N/A	BR102	TF	101.62° Mag 79.50° True	N/A	N/A	+13000	N/A	N/A	20.40	N/A	OTHER	RNAV 1 or RNP 1
30	UGTAK	N	N/A	SIMUV	TF	101.91° Mag 79.69° True	N/A	N/A	N/A	N/A	N/A	17.64	N/A	OTHER	RNAV 1 or RNP 1
40	UGTAK	N	N/A	UGTAK	TF	81.66° Mag 59.36° True	N/A	N/A	N/A	N/A	N/A	75.99	N/A	OTHER	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
DIBUB	S 15:52:22.00W 48:04:17.96
UTPAS	S 15:40:21.60W 47:59:33.60
ILKUS	S 14:55:23.00W 48:11:56.00
PULUV	S 14:39:01.75W 47:39:26.25
EPDEP	S 14:46:47.98W 47:00:21.46
BR102	S 15:36:36.63W 47:38:46.77
SIMUV	S 15:33:25.72W 47:20:47.90
UGTAK	S 14:54:21.95W 46:13:16.59

DER	Latitude / Longitude (WGS84) DD:MM:SS.SS	Elevation (FT)
29R	S 15:51:48.86 W 47:55:39.22	3447.60

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE