



CODING TABLE

IAC RNP W RWY 29L (AR)					BRASÍLIA / Pres. Juscelino Kubitschek, INTL (SBBR)						SBBR_IAC_03Z	29 OCT 26			
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	MOPDA	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP 1.0
20	APCH	N	N/A	BR096	TF	13.73° Mag 351.49° True	N/A	N/A	+6500	N/A	N/A	3.73	N/A	OTHER	RNP 1.0
30	APCH	N	N/A	TOGIG	TF	318.34° Mag 296.11° True	N/A	N/A	+6500	N/A	N/A	3.90	N/A	IF	RNP 1.0
10	APCH	N/A	N/A	EDVIV	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP 1.0
20	APCH	N	N/A	TOGIG	TF	218.37° Mag 196.15° True	N/A	N/A	+6500	N/A	N/A	7.04	N/A	IF	RNP 1.0
10	FINAL	N/A	N/A	TOGIG	IF	N/A	N/A	N/A	+6500	N/A	N/A	N/A	N/A	IF	RNP 1.0
20	FINAL	N	N/A	ARVER	TF	288.36° Mag 266.15° True	N/A	N/A	+6500	N/A	N/A	2.92	N/A	OTHER	RNP 1.0
30	FINAL	N	N/A	BR002	TF	288.36° Mag 266.16° True	N/A	N/A	+6000	N/A	N/A	2.79	N/A	FAF	RNP 1.0
40	FINAL	Y	N/A	RW29L	TF	288.33° Mag 266.15° True	N/A	N/A	@3472	N/A	N/A	7.94	-3.00	LTP	RNP 0.24
10	MA	N	N/A	BR093	TF	288.33° Mag 266.15° True	N/A	N/A	N/A	N/A	N/A	1.70	N/A	OTHER	RNP 0.24
20	MA	N	N/A	BR094	TF	258.34° Mag 236.20° True	L	N/A	N/A	N/A	N/A	8.88	N/A	OTHER	RNP 1.0
30	MA	Y	N/A	SIPIG	TF	278.26° Mag 256.19° True	R	N/A	+7000	N/A	N/A	6.86	N/A	MAHF	RNP 1.0
40	MA	Y	N/A	SIPIG	HM	98.26° Mag 76.20° True	R	N/A	+7000	N/A	N/A	1.00 min	N/A	MAHF	RNP 1.0

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
MOPDA	S 15:57:14.02W 47:36:18.72
BR096	S 15:53:32.04W 47:36:52.99
TOGIG	S 15:51:48.66W 47:40:30.82
BR002	S 15:52:11.67W 47:46:25.35
BR093	S 15:52:50.41W 47:56:23.96
BR094	S 15:57:47.89W 48:04:03.54
SIPIG	S 15:59:26.73W 48:10:58.58
EDVIV	S 15:45:01.37W 47:38:28.96
RW29L	S 15:52:43.62W 47:54:38.33
ARVER	S 15:52:00.44W 47:43:32.05

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT

SPECIAL PARAMETERS TABLE

This table contains the parameter values that differ from the standard values established in RNP AR Manual (Doc 9905) and/or PANS-OPS (Doc 8168) and has the objective to assist operators during the approval process by the competent Aeronautical Authority, especially regarding the Flight Operational Safety Assessment. These parameters take into account only design criteria contained in Doc 9905 and Doc 8168. Airworthiness special parameters were not considered for this classification.

[illegible]

MISSED APPROACH SEGMENT															
Track	Bank Angle(°)		TWC (KT)		IAS (KT)		D _{MASRNP} (NM)		TrD (NM)		Gradient (%)		RNP (NM)		TP Altitude (FT)
	Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD
ALL PARAMETERS ARE ACCORDING TO ICAO DOCUMENTS															

COD	Meaning
STD	Value according to ICAO Documents
TWC	Tail Wind Component
IAS	Indicated Air Speed
D _{frop}	Distance FROP-THEL
FROP	Final Roll-Out Point
TrD	Track Distance (Needed to comply turns)
TP Altitude	Turning Point Altitude
THEL	Threshold elevation
D _{MASRNP}	Maximum distance of RNP navigation accuracy (requirement less than 1.0 NM in the missed approach)