



CODING TABLE

IAC RNP Z RWY 32					BAURU / Bauru (SBBU)							SBBU_IAC_00M		11 JUN 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role Of TheFix	Navigation Specification
10	APCH	N/A	N/A	BU018	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	BU017	TF	338.55° Mag 317.82° True	N/A	N/A	+4000	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	BU019	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	BU017	TF	68.55° Mag 47.82° True	N/A	N/A	+4000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	BU017	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	BU016	TF	338.55° Mag 317.84° True	N/A	N/A	R3670	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	BU001*	TF	323.55° Mag 302.86° True	L	N/A	+2760	N/A	N/A	2.84	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY32	TF	323.55° Mag 302.87° True	N/A	N/A	@2072	N/A	N/A	2.16	-3.00	LTP	RNP APCH
10	MA	N	N/A	BU011	TF	323.55° Mag 302.90° True	N/A	N/A	N/A	N/A	N/A	5.70	N/A	OTHER	RNP APCH
20	MA	Y	N/A	BU013	TF	308.29° Mag 287.97° True	L	N/A	+5000	N/A	N/A	10.00	N/A	MAHF	RNP APCH
30	MA	Y	N/A	BU013	HM	128.28° Mag 107.97° True	R	N/A	+5000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

* Fictitious point: Only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BU018	S 22:31:04.67W 48:51:04.59
BU017	S 22:27:21.64W 48:54:42.16
BU019	S 22:31:24.14W 48:59:30.30
BU016	S 22:23:38.52W 48:58:19.55
BU001	S 22:22:05.64W 49:00:54.23
RWY32	S 22:20:55.20W 49:02:51.45
BU011	S 22:17:48.70W 49:08:01.46
BU013	S 22:14:43.30W 49:18:16.92

COD	Meaning
+	AT OR ABOVE
N/A	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT