



CODING TABLE

SID RNAV EGBAM 1F RWY 31					CANOAS / Campo Nossa Senhora de Fátima, MIL (SBCO)							SBCO_SID_02N		16 APR 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	RWY	N	N/A	DEVAV	CF	307.28° Mag 289.53° True	N/A	N/A	N/A	210	-	6.30	N/A	OTHER	RNAV 1 or RNP 1
20	RWY	N	N/A	EGBAM	TF	200.39° Mag 182.76° True	N/A	B6000	B5000	N/A	N/A	15.80	N/A	OTHER	RNAV 1 or RNP 1
10	DEVOT	N/A	N/A	EGBAM	IF	N/A	N/A	B6000	B5000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	DEVOT	N	N/A	AMVOM	TF	237.34° Mag 220.06° True	N/A	N/A	N/A	N/A	N/A	25.97	N/A	OTHER	RNAV 1 or RNP 1
30	DEVOT	N	N/A	DOVNA	TF	252.37° Mag 235.33° True	N/A	N/A	N/A	N/A	N/A	17.50	N/A	OTHER	RNAV 1 or RNP 1
40	DEVOT	N	N/A	DEVOT	TF	249.25° Mag 233.01° True	N/A	N/A	N/A	N/A	N/A	55.40	N/A	OTHER	RNAV 1 or RNP 1
10	ISOBU	N/A	N/A	EGBAM	IF	N/A	N/A	B6000	B5000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	ISOBU	N	N/A	AMVOM	TF	237.34° Mag 220.06° True	N/A	N/A	N/A	N/A	N/A	25.97	N/A	OTHER	RNAV 1 or RNP 1
30	ISOBU	N	N/A	DOVNA	TF	252.37° Mag 235.33° True	N/A	N/A	N/A	N/A	N/A	17.50	N/A	OTHER	RNAV 1 or RNP 1
40	ISOBU	N	N/A	TOKAK	TF	284.83° Mag 268.37° True	N/A	N/A	N/A	N/A	N/A	47.90	N/A	OTHER	RNAV 1 or RNP 1
50	ISOBU	N	N/A	ISOBU	TF	282.17° Mag 266.10° True	N/A	N/A	N/A	N/A	N/A	29.68	N/A	OTHER	RNAV 1 or RNP 1
10	TOKAK	N/A	N/A	EGBAM	IF	N/A	N/A	B6000	B5000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	TOKAK	N	N/A	AMVOM	TF	237.34° Mag 220.06° True	N/A	N/A	N/A	N/A	N/A	25.97	N/A	OTHER	RNAV 1 or RNP 1
30	TOKAK	N	N/A	DOVNA	TF	252.37° Mag 235.33° True	N/A	N/A	N/A	N/A	N/A	17.50	N/A	OTHER	RNAV 1 or RNP 1
40	TOKAK	N	N/A	TOKAK	TF	284.83° Mag 268.37° True	N/A	N/A	N/A	N/A	N/A	47.90	N/A	OTHER	RNAV 1 or RNP 1
10	POXEV	N/A	N/A	EGBAM	IF	N/A	N/A	B6000	B5000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	POXEV	N	N/A	AMVOM	TF	237.34° Mag 220.06° True	N/A	N/A	N/A	N/A	N/A	25.97	N/A	OTHER	RNAV 1 or RNP 1

30	POXEV	N	N/A	DOVNA	TF	252.37° Mag 235.33° True	N/A	N/A	N/A	N/A	N/A	17.50	N/A	OTHER	RNAV 1 or RNP 1
40	POXEV	N	N/A	POXEV	TF	300.96° Mag 284.73° True	N/A	N/A	N/A	N/A	N/A	83.90	N/A	OTHER	RNAV 1 or RNP 1
10	TEMEK	N/A	N/A	EGBAM	IF	N/A	N/A	B6000	B5000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	TEMEK	N	N/A	EDSEP	TF	222.71° Mag 204.71° True	N/A	N/A	N/A	N/A	N/A	21.64	N/A	OTHER	RNAV 1 or RNP 1
30	TEMEK	N	N/A	TEMEK	TF	243.18° Mag 225.89° True	N/A	N/A	N/A	N/A	N/A	6.50	N/A	OTHER	RNAV 1 or RNP 1

SID RNAV SUSKI 1F RWY 31					CANOAS / Campo Nossa Senhora de Fátima, MIL (SBCO)							SBCO_SID_02N		16 APR 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	SUSKI	N	N/A	DEVAV	CF	307.28° Mag 289.53° True	N/A	N/A	N/A	210	-	6.30	N/A	OTHER	RNAV 1 or RNP 1
20	SUSKI	N	N/A	CO019	TF	307.23° Mag 289.66° True	N/A	-11000	N/A	N/A	N/A	22.10	N/A	OTHER	RNAV 1 or RNP 1
30	SUSKI	N	N/A	ORAKI	TF	307.35° Mag 289.83° True	N/A	N/A	N/A	N/A	N/A	7.13	N/A	OTHER	RNAV 1 or RNP 1
40	SUSKI	N	N/A	SUSKI	TF	281.67° Mag 264.41° True	N/A	N/A	N/A	N/A	N/A	20.78	N/A	OTHER	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
DEVAV	S 29:54:24.02W 51:16:18.08
EGBAM	S 30:10:13.41W 51:17:10.65
EDSEP	S 30:29:56.42W 51:27:36.82
TEMEK	S 30:34:28.80W 51:33:01.20
AMVOM	S 30:30:10.09W 51:36:27.30
DOVNA	S 30:40:10.00W 51:53:07.20
DEVOT	S 31:13:44.50W 52:44:25.58
TOKAK	S 30:41:43.67W 52:48:38.51
ISOBU	S 30:43:49.67W 53:22:58.86
POXEV	S 30:19:20.70W 53:27:12.77
CO019	S 29:46:59.09W 51:40:14.57
ORAKI	S 29:44:33.93W 51:47:56.76
SUSKI	S 29:46:37.82W 52:11:41.87

DER	Latitude / Longitude (WGS84) DD:MM:SS.SS	Elevation (FT)
31	S 29:56:30.53 W 51:09:28.04	17.55

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT