



CODING TABLE

IAC ILS W RWY 28					RIO DE JANEIRO / Galeão - Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_00Z		27 NOV 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	SEDBU	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	LIXUG	TF	187.71° Mag 164.52° True	N/A	N/A	+2800	N/A	N/A	5.50	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	KETUX	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	LIXUG	TF	277.32° Mag 254.10° True	N/A	N/A	+2800	N/A	N/A	5.54	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	LIXUG	IF	N/A	N/A	N/A	+2800	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ILM	VUBOP	CF	277.74° Mag 254.61° True	N/A	N/A	R1680	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	ILM	RWY28	CF	277.74° Mag 254.61° True	N/A	N/A	@80	N/A	N/A	5.01	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	VA	277.73° Mag 254.59° True	N/A	N/A	+600	210	-	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	MA	N	N/A	GL086	DF	N/A	R	-4000	N/A	210	-	N/A	N/A	OTHER	RNAV 1 or RNP 1
30	MA	N	N/A	GL087	TF	97.35° Mag 74.15° True	N/A	N/A	N/A	210	-	5.54	N/A	OTHER	RNAV 1 or RNP 1
40	MA	Y	N/A	KETUX	TF	187.82° Mag 164.60° True	R	N/A	+5000	210	-	7.50	N/A	MAHF	RNAV 1 or RNP 1
50	MA	Y	N/A	KETUX	HM	277.32° Mag 254.10° True	L	N/A	+5000	N/A	N/A	1.00 min	N/A	MAHF	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
LIXUG	S 22:44:51.60W 43:02:37.20
VUBOP	S 22:46:11.88W 43:07:50.07
RWY28	S 22:47:31.84W 43:13:03.50
SEDBU	S 22:39:32.41W 43:04:12.51
KETUX	S 22:43:20.40W 42:56:51.60
GL086	S 22:37:36.12W 43:04:46.18
GL087	S 22:36:05.00W 42:59:00.86

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE