



CODING TABLE

IAC ILS U CAT II RWY 10					RIO DE JANEIRO / Galeão – Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_01H		29 OCT 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	BITOX	IF	N/A	N/A	N/A	+6400	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	ITB	SUNSI	CF	96.86° Mag 73.80° True	N/A	N/A	+3900	N/A	N/A	6.77	N/A	OTHER	N/A
30	APCH	N/A	ITB	GAVUG	CF	96.87° Mag 73.81° True	N/A	N/A	+3500	N/A	N/A	1.50	N/A	IF	N/A
10	FINAL	N/A	N/A	GAVUG	IF	N/A	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ITB	GL008*	CF	96.87° Mag 73.81° True	N/A	N/A	+2800	N/A	N/A	2.00	N/A	SDF	N/A
30	FINAL	N/A	ITB	GL167	CF	96.87° Mag 73.81° True	N/A	N/A	R1670	N/A	N/A	3.74	N/A	FAF	N/A
40	FINAL	N/A	ITB	RWY10	CF	96.77° Mag 73.71° True	N/A	N/A	@76	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	CA	96.79° Mag 73.73° True	N/A	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	PCX	DF	N/A	R	N/A	+7000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	PCX	PCX	HM	291.86° Mag 268.80° True	R	N/A	+7000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR/DME PCX	S 22:42:55.42W 42:51:26.72
BITOX	S 22:53:09.60W 43:35:09.00
SUNSI	S 22:51:22.00W 43:28:05.04
GAVUG	S 22:50:57.98W 43:26:31.11
GL008	S 22:50:26.08W 43:24:25.84
GL167	S 22:49:26.40W 43:20:31.80
RWY10	S 22:48:06.66W 43:15:18.62

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT