



## CODING TABLE

IAC VOR Z RWY 12					MACEIÓ / Zumbi dos Palmares, INTL (SBMO)							SBMO_IAC_00J		09 JUL 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	MCE	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	MCE	MCE	FC	325.84° Mag 304.12° True	N/A	N/A	+2100	N/A	N/A	10.00	N/A	OTHER	N/A
30	APCH	N/A	MCE	ISODU	CF	120.57° Mag 98.85° True	L	N/A	R1730	N/A	N/A	N/A	N/A	FAF	N/A
10	FINAL	N/A	N/A	ISODU	IF	N/A	N/A	N/A	R1730	N/A	N/A	N/A	N/A	FAF	N/A
20	FINAL	N/A	MCE	MCE02*	CF	120.57° Mag 98.85° True	N/A	N/A	@438	N/A	N/A	4.03	-3.00	FTP	N/A
10	MA	N/A	MCE	N/A	CA	120.57° Mag 98.85° True	N/A	N/A	+1700	N/A	N/A	N/A	N/A	N/A	N/A
20	MA	N/A	N/A	MCE	DF	N/A	L	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	MCE	MCE	HM	326.00° Mag 304.28° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR/DME MCE	S 09:30:35.62W 35 47:12.74
MCE02*	S 09:30:27.45W 35 48:11.32
ISODU	S 09:29:53.60W 35:52:13.64

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT