



CODING TABLE

IAC VOR Z RWY 11					PORTO ALEGRE / Salgado Filho, INTL (SBPA)							SBPA_IAC_01F		16 APR 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	FIG	EDSOL	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	FIG	PANIB	AF	N/A	L	N/A	+6000	N/A	N/A	N/A	N/A	IAF	N/A
30	APCH	N/A	FIG	PA008*	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	N/A
40	APCH	N/A	FIG	POSBI	CF	109.03° Mag / 91.17° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	N/A
10	APCH	N/A	FIG	ISTEN	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	FIG	VUBRA	AF	N/A	R	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
30	APCH	N/A	FIG	PA009*	AF	N/A	R	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	N/A
40	APCH	N/A	FIG	POSBI	CF	109.03° Mag / 91.17° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	N/A
10	FINAL	N/A	N/A	POSBI	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	FIG	ISEPA	CF	109.03° Mag / 91.17° True	N/A	N/A	R1720	N/A	N/A	2.19	N/A	FAF	N/A
30	FINAL	N/A	FIG	PA098*	CF	109.03° Mag / 91.16° True	N/A	N/A	R794	N/A	N/A	2.90	-3.00	SDF	N/A
40	FINAL	N/A	FIG	RWY11	CF	109.01° Mag / 91.15° True	N/A	N/A	@61	N/A	N/A	2.30	-3.00	LTP	N/A
10	MA	N/A	FIG	FIG	CF	109.03° Mag / 91.17° True	N/A	N/A	N/A	N/A	N/A	10.80	N/A	OTHER	N/A
20	MA	N/A	FIG	ENTAB	CF	140.28° Mag / 122.43° True	R	N/A	+4000	N/A	N/A	7.26	N/A	MAHF	N/A
30	MA	N/A	FIG	ENTAB	HM	140.28° Mag / 122.43° True	L	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR/DME FIG	S 29:59:53.44W 50:58:31.96
POSBI	S 29:59:29.40W 51:19:29.40
ISEPA	S 29:59:32.40W 51:16:58.20
EDSOL	S 29:45:23.42W 50:41:01.30
PANIB	S 29:44:45.44W 51:15:19.36
PA008	S 29:59:25.32W 51:22:42.61
ISTEN	S 30:15:49.67W 51:14:21.21
VUBRA	S 30:08:19.26W 51:20:42.52
PA009	S 29:59:25.21W 51:22:42.61
PA098	S 29:59:36.40W 51:13:37.71
ENTAB	S 30:03:47.40W 50:51:28.20

COD	Meaning
+	AT OR ABOVE
N/A	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT