



CODING TABLE

IAC VOR Y RWY 29					PORTO ALEGRE / Salgado Filho, INTL (SBPA)							SBPA_IAC_01G		16 APR 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	KOTUB	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	FIG	FIG	CF	222.36° Mag 204.50° True	N/A	N/A	+2200	N/A	N/A	6.14	N/A	IF	N/A
10	APCH	N/A	N/A	VUGBO	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	FIG	FIG	CF	354.98° Mag 337.12° True	N/A	N/A	+2200	N/A	N/A	6.17	N/A	IF	N/A
10	FINAL	N/A	N/A	FIG	IF	N/A	N/A	N/A	+2200	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	FIG	NETPI	CF	288.96° Mag 271.11° True	N/A	N/A	R1520	N/A	N/A	4.58	N/A	FAF	N/A
30	FINAL	N/A	FIG	PA031*	CF	288.79° Mag 270.93° True	N/A	N/A	R812	N/A	N/A	2.28	-3.00	SDF	N/A
40	FINAL	N/A	FIG	RWY29	CF	289.00° Mag / 271.14° True	N/A	N/A	@80	N/A	N/A	2.30	-3.00	LTP	N/A
10	MA	N/A	FIG	ALCIR	CF	288.85° Mag / 271.00° True	N/A	N/A	N/A	N/A	N/A	12.66	N/A	OTHER	N/A
20	MA	N/A	CXS	DAKAT	CF	210.71° Mag / 192.63° True	L	N/A	+4000	N/A	N/A	5.69	N/A	MAHF	N/A
30	MA	N/A	FIG	DAKAT	HM	95.17° Mag / 77.31° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR/DME FIG	S 29:59:53.44W 50:58:31.96
NETPI	S 29:59:48.00W 51:03:48.60
ALCIR	S 29:59:28.28W 51:23:33.97
DAKAT	S 30:05:01.80W 51:25:00.60
KOTUB	S 29:54:18.60W 50:55:32.40
VUGBO	S 30:05:36.60W 50:55:49.80
RWY29	S 29:59:42.14W 51:08:59.46
PA031	S 29:59:45.31W 51:06:20.57

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT