



CODING TABLE

IAC RNP RWY 25					RIO BRANCO / Plácido de Castro, INTL (SBRB)							SBRB_IAC_00J		30 OCT 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	RB011	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	RB007	TF	178.39° Mag 167.07° True	N/A	N/A	+3000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	RB009	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	RB007	TF	248.37° Mag 237.05° True	N/A	N/A	+3000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	RB008	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	RB007	TF	318.42° Mag 307.10° True	N/A	N/A	+3000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	RB007	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	RB013	TF	248.39° Mag 237.14° True	N/A	N/A	R2240	N/A	N/A	5.01	N/A	FAF	RNP APCH
30	FINAL	N	N/A	RB035*	TF	248.34° Mag 237.12° True	N/A	N/A	R1378	N/A	N/A	2.70	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY25	TF	248.32° Mag 237.13° True	N/A	N/A	@647	N/A	N/A	2.30	-3.00	MAPT	RNP APCH
10	MA	Y	N/A	RB004	CF	248.19° Mag 237.15° True	N/A	N/A	+3000	N/A	N/A	11.16	N/A	MAHF	RNP APCH
20	MA	Y	N/A	RB004	HM	68.38° Mag 57.33° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
RB004	S 09:57:54.60W 68:02:38.40
RB011	S 09:40:29.40W 67:45:59.40
RB007	S 09:46:22.20W 67:44:37.80
RB009	S 09:43:05.40W 67:39:31.80
RB013	S 09:49:06.00W 67:48:53.40
RB008	S 09:50:00.00W 67:39:47.40
RB035	S 09:50:34.35W 67:51:11.22
RWY25	S 09:51:49.45W 67:53:08.40

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT