



CODING TABLE

SID RNP EVK0X 2F RWY 02R/20L (AR)					RIO DE JANEIRO / Santos Dumont (SBRJ)							SBRJ_SID_02J		26 NOV 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	RWY20	N	N/A	RJ006	TF	199.56° Mag 176.55° True	N/A	N/A	+400	N/A	N/A	0.30	2.86	OTHER	RNP 0.3
20	RWY20	N/A	N/A	RJ076	RF	N/A	L	N/A	N/A	N/A	N/A	1.40	2.86	OTHER	RNP 0.3
N/A	N/A	N/A	N/A	RJ077*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	ARC RADIUS 1.20	N/A	RF CENTER	N/A
30	RWY20	N/A	N/A	RJ078	RF	N/A	R	N/A	+1400	150	-	1.11	2.86	OTHER	RNP 0.3
N/A	N/A	N/A	N/A	RJ079*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	ARC RADIUS 2.00	N/A	RF CENTER	N/A
40	RWY20	N	N/A	EVS0B	TF	164.32° Mag 141.30° True	N/A	N/A	N/A	N/A	N/A	3.73	2.86	OTHER	RNP 1
10	RWY02	N	N/A	RJ016	TF	19.57° Mag 356.55° True	N/A	N/A	+400	N/A	N/A	0.50	2.46	OTHER	RNP 0.3
20	RWY02	N	N/A	RJ022	RF	N/A	R	N/A	N/A	N/A	N/A	2.73	2.46	OTHER	RNP 0.3
N/A	N/A	N/A	N/A	RJ026*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	ARC RADIUS 1.50	N/A	RF CENTER	RNP 0.3
30	RWY02	N	N/A	MALDU	TF	123.71° Mag 100.68° True	N/A	N/A	+2500	N/A	N/A	4.90	2.46	OTHER	RNP 1
40	RWY02	N	N/A	UTGAT	TF	193.13° Mag 170.08° True	N/A	N/A	N/A	N/A	N/A	3.17	2.46	OTHER	RNP 1
50	RWY02	N	N/A	EVS0B	TF	242.68° Mag 219.64° True	N/A	N/A	N/A	N/A	N/A	4.74	2.46	OTHER	RNP 1
10	COMMON	N/A	N/A	EVS0B	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNP 1
20	COMMON	Y	N/A	EVK0X	TF	242.61° Mag 219.59° True	N/A	B8000	B5000	N/A	N/A	5.26	N/A	OTHER	RNP 1
10	ESORU	N/A	N/A	EVK0X	IF	N/A	N/A	B8000	B5000	N/A	N/A	N/A	N/A	OTHER	RNP 1
20	ESORU	N	N/A	DOVDA	TF	335.36° Mag 312.36° True	N/A	N/A	+10000	N/A	N/A	13.42	N/A	OTHER	RNP 1
30	ESORU	N	N/A	EVLOG	TF	334.28° Mag 311.30° True	N/A	N/A	+14000	N/A	N/A	8.80	N/A	OTHER	RNP 1

40	ESORU	N	N/A	RJ003	TF	334.35° Mag 311.39° True	N/A	N/A	N/A	N/A	N/A	9.89	N/A	OTHER	RNP 1
50	ESORU	N	N/A	RJ004	TF	284.59° Mag 261.69° True	N/A	N/A	N/A	N/A	N/A	10.74	N/A	OTHER	RNP 1
60	ESORU	N	N/A	ESORU	TF	273.18° Mag 250.29° True	N/A	N/A	N/A	N/A	N/A	53.06	N/A	OTHER	RNP 1
10	NAXOP	N/A	N/A	EVKOX	IF	N/A	N/A	B8000	B5000	N/A	N/A	N/A	N/A	OTHER	RNP 1
20	NAXOP	N	N/A	TIVRO	TF	241.83° Mag 218.83° True	N/A	N/A	N/A	N/A	N/A	20.70	N/A	OTHER	RNP 1
30	NAXOP	N	N/A	ARSOV	TF	278.60° Mag 255.70° True	N/A	N/A	+24000	N/A	N/A	31.00	N/A	OTHER	RNP 1
40	NAXOP	N	N/A	NAXOP	TF	278.66° Mag 255.91° True	N/A	N/A	N/A	N/A	N/A	12.91	N/A	OTHER	RNP 1
10	BITAK	N/A	N/A	EVKOX	IF	N/A	N/A	B8000	B5000	N/A	N/A	N/A	N/A	OTHER	RNP 1
20	BITAK	N	N/A	TIVRO	TF	241.83° Mag 218.83° True	N/A	N/A	N/A	N/A	N/A	20.70	N/A	OTHER	RNP 1
30	BITAK	N	N/A	BITAK	TF	241.23° Mag 218.32° True	N/A	N/A	N/A	N/A	N/A	22.46	N/A	OTHER	RNP 1

*Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
RJ006	S 22:55:17.51 W 43:09:43.61
RJ076	S 22:56:21.00 W 43:08:52.00
RJ077	S 22:55:13.19 W 43:08:25.76
RJ078	S 22:56:59.34 W 43:07:54.26
RJ079	S 22:58:14.61 W 43:09:35.75
EVS0B	S 22:59:54.64 W 43:05:22.58
EVK0X	S 23:03:58.68 W 43:09:00.75
DOVDA	S 22:54:53.69 W 43:19:45.39
EVLOG	S 22:49:03.80 W 43:26:54.70
RJ003	S 22:42:29.79 W 43:34:56.27
RJ004	S 22:44:03.15 W 43:46:25.82
ESORU	S 23:01:50.97 W 44:40:35.45
TIVRO	S 23:20:08.73 W 43:23:06.88
ARSOV	S 23:27:46.22 W 43:55:47.16
NAXOP	S 23:30:54.70 W 44:09:24.54
UTGAT	S 22:56:15.00 W 43:02:06.00
BITAK	S 23:37:48.60 W 43:38:16.80
RJ016	S 22:53:46.51 W 43:09:49.51
RJ022	S 22:52:12.37 W 43:07:54.06
RJ026	S 22:53:41.10 W 43:08:12.21
MALDU	S 22:53:06.92 W 43:02:41.50
RJ038	S 22:54:59.49 W 43:09:44.78
RJ039	S 22:54:16.55 W 43:09:47.56

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT

DER	Latitude / Longitude (WGS84) DD:MM:SS.SS	Elevation (FT)
02R	S 22:54:16.56 W 43:09:47.55	10.00
20L	S 22:54:59.48 W 43:09:44.78	9.42

SPECIAL PARAMETERS TABLE

This table contains the parameter values that differ from the standard values established in RNP AR Manual (Doc 9905) and/or PANS-OPS (Doc 8168) and has the objective to assist operators during the approval process by the competent Aeronautical Authority, especially regarding the Flight Operational Safety Assessment. These parameters take into account only design criteria contained in Doc 9905 and Doc 8168. Airworthiness special parameters were not considered for this classification.

[illegible]

MISSED APPROACH SEGMENT																
Track	Bank Angle(°)		TWC (KT)		IAS (KT)		D _{MASRNP} (NM)		TrD (NM)		Gradient (%)		RNP (NM)		TP Altitude (FT)	
	Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD		Used / STD	
ALL PARAMETERS ARE ACCORDING TO ICAO DOCUMENTS																

COD	Meaning
STD	Value according to ICAO Documents
TWC	Tail Wind Component
IAS	Indicated Air Speed
D _{frop}	Distance FROP-THEL
FROP	Final Roll-Out Point
TrD	Track Distance (Needed to comply turns)
TP Altitude	Turning Point Altitude
THEL	Threshold elevation
D _{MASRNP}	Maximum distance of RNP navigation accuracy (requirement less than 1.0 NM in the missed approach)