



## CODING TABLE

IAC VOR RWY 08					TAUBATÉ / Base de Aviação de Taubaté, MIL (SBTA)							SBTA_IAC_00M		03 OCT 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	TAU	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	N/A	PI	252.00° Mag 229.88° True	R	N/A	+4400	N/A	N/A	6.02	N/A	OTHER	N/A
30	APCH	N/A	N/A	ANPUP	CF	72.00° Mag 49.88° True	N/A	N/A	+4400	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	ANPUP	IF	N/A	N/A	N/A	+4400	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	TAU	IROSO	CF	72.00° Mag 49.88° True	N/A	N/A	R3420	N/A	N/A	2.50	N/A	FAF	N/A
30	FINAL	N/A	TAU	TAU09*	CF	72.00° Mag 49.88° True	N/A	N/A	R2921	N/A	N/A	1.00	-4.63	SDF	N/A
40	FINAL	N/A	TAU	TAU08*	CF	72.00° Mag 49.88° True	N/A	N/A	@1937	N/A	N/A	2.00	-4.63	FTP	N/A
10	MA	N/A	TAU	N/A	CA	72.00° Mag 49.88° True	N/A	N/A	+4000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	TAU	DF	N/A	L	N/A	+6000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	TAU	TAU	HM	252.00° Mag 229.87° True	R	N/A	+6000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ANPUP	S 23:06:01.98W 45:35:44.64
IROSO	S 23:04:25.04W 45:33:40.20
TAU09	S 23:03:46.25W 45:32:50.43
TAU08	S 23:02:28.67W 45:31:10.93
VOR TAU	S 23:02:08.55W 45:30:45.13

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT