



CODING TABLE

IAC RNP RWY 02					TELÉMACO BORBA / Telémaco Borba (SSVL)							SSVL_IAC_00B		27 NOV 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	VL003	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL002	TF	291.67° Mag / 271.65° True	N/A	N/A	+4400	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VL004	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL002	TF	111.65° Mag / 91.74° True	N/A	N/A	+4400	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VL006	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL002	TF	21.64° Mag / 1.70° True	N/A	N/A	+4400	N/A	N/A	5.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	VL002	IF	N/A	N/A	N/A	+4400	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	VL001	TF	21.66° Mag / 1.69° True	N/A	N/A	R4250	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	VL007*	TF	21.69° Mag / 1.69° True	N/A	N/A	R3384	N/A	N/A	2.70	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY02	TF	21.70° Mag / 1.69° True	N/A	N/A	@2652	N/A	N/A	2.30	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	21.71° Mag / 1.69° True	N/A	N/A	+3600	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	VL004	DF	N/A	L	N/A	+5500	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	VL004	HM	112.00° Mag / 92.09° True	L	N/A	+5500	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
RWY02	S 24:19:26.05W 50:39:07.20
VL004	S 24:29:16.89W 50:46:01.10
VL002	S 24:29:27.71W 50:39:26.63
VL001	S 24:24:26.88W 50:39:16.91
VL007	S 24:21:44.43W 50:39:11.66
VL003	S 24:29:38.25W 50:32:52.14
VL006	S 24:34:28.54W 50:39:36.36

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT