



CODING TABLE

IAC RNP RWY 20					TELÉMACO BORBA / Telémaco Borba (SSVL)							SSVL_IAC_00C		27 NOV 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	VL011	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL012	TF	291.76° Mag / 271.64° True	N/A	N/A	+4200	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VL009	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL012	TF	201.78° Mag / 181.69° True	N/A	N/A	+4200	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VL008	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VL012	TF	111.74° Mag / 91.73° True	N/A	N/A	+4200	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	VL012	IF	N/A	N/A	N/A	+4200	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	VL013	TF	201.75° Mag / 181.69° True	N/A	N/A	+4200	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	VL014*	TF	201.73° Mag / 181.69° True	N/A	N/A	R3331	N/A	N/A	2.70	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY20	TF	201.72° Mag / 181.69° True	N/A	N/A	@2599	N/A	N/A	2.30	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	201.71° Mag / 181.69° True	N/A	N/A	+3400	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	VL008	DF	N/A	R	N/A	+5500	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	VL008	HM	111.74° Mag / 91.73° True	R	N/A	+5500	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VL012	S 24:08:33.20W 50:38:46.18
VL013	S 24:13:34.04W 50:38:55.86
VL014	S 24:16:16.49W 50:39:01.09
RWY20	S 24:18:34.88W 50:39:05.55
VL009	S 24:03:32.36W 50:38:36.51
VL008	S 24:08:22.43W 50:45:19.58
VL011	S 24:08:43.70W 50:32:12.76

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT