



## CODING TABLE

IAC VOR Y RWY 29					MANAUS / Eduardo Gomes, INTL (SBEG)							SBEG_IAC_00K		29 DEC 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	DAGTI	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	EGN96*	AF	N/A	R	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	MNS	LOBUX	CF	286.25° Mag / 269.81° True	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	EG011	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	MNS	LOBUX	CF	286.25° Mag / 269.81° True	N/A	N/A	+2000	N/A	N/A	5.00	N/A	IF	N/A
10	FINAL	N/A	N/A	LOBUX	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	MNS	LODEG	CF	286.25° Mag / 269.81° True	N/A	N/A	R1910	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	MNS	EGN97*	CF	286.25° Mag / 269.81° True	N/A	N/A	R1461	N/A	N/A	1.40	N/A	SDF	N/A
40	FINAL	N/A	MNS	EGN98*	CF	286.25° Mag / 269.81° True	N/A	N/A	@313	N/A	N/A	3.60	N/A	FTP	N/A
10	MA	N/A	MNS	N/A	CA	286.26° Mag / 269.82° True	N/A	N/A	+2000	230	-	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	120.00° Mag / 103.65° True	R	N/A	N/A	230	-	N/A	N/A	OTHER	N/A
30	MA	N/A	MNS	DAGTI	CF	77.76° Mag / 61.23° True	L	N/A	+4000	230	-	N/A	N/A	MAHF	N/A
40	MA	N/A	MNS	DAGTI	HM	257.66° Mag / 241.23° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
EG011	S 03:02:20.87W 59:47:15.55
LODEG	S 03:02:22.92W 59:57:15.30
LOBUX	S 03:02:21.91W 59:52:15.40
EGN96	S 03:02:21.58W 59:50:41.41
EGN97	S 03:02:23.20W 59:58:39.06
EGN98*	S 03:02:23.91W 60:02:15.17
RWY29	S 03:02:19.03W 60:02:15.19
DAGTI	S 02:56:18.51W 59:52:14.72

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE