



CODING TABLE

IAC RNP RWY 26					GUARAPUAVA / Tancredo Thómas de Faria (SSGG)							SSGG_IAC_00E		01 DEC 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	GU012	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	GU008	TF	172.27° Mag 153.54° True	N/A	N/A	+5200	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	GU009	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	GU008	TF	262.28° Mag 243.55° True	N/A	N/A	+5200	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	GU011	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	GU008	TF	352.27° Mag 333.54° True	N/A	N/A	+5200	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	GU008	IF	N/A	N/A	N/A	+5200	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	GU007	TF	262.26° Mag 243.58° True	N/A	N/A	R5130	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	GU013*	TF	262.24° Mag 243.60° True	N/A	N/A	R4235	N/A	N/A	2.80	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY26	TF	262.23° Mag 243.62° True	N/A	N/A	@3534	N/A	N/A	2.20	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	262.22° Mag 243.62° True	N/A	N/A	+5300	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	GU012	DF	N/A	R	N/A	+7000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	GU012	HM	172.28° Mag 153.55° True	L	N/A	+7000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point: Only for coding purposes

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
GU008	S 25:18:40.51W 51:21:09.36
GU007	S 25:20:54.47W 51:26:05.86
GU013	S 25:22:09.42W 51:28:51.97
GU012	S 25:13:17.20W 51:24:06.27
GU009	S 25:16:26.38W 51:16:13.05
GU011	S 25:24:03.75W 51:18:12.19
RWY26	S 25:23:08.27W 51:31:02.53

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT