



CODING TABLE

IAC ILS Z or LOC Z RWY 12					MACEIÓ / Zumbi dos Palmares, INTL (SBMO)							SBMO_IAC_00H		28 NOV 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	PUDAL	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	UTNEB	AF	N/A	R	N/A	+2200	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	VAKIK	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	UTNEB	AF	N/A	L	N/A	+2200	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	EKATA	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	UTNEB	AF	N/A	R	N/A	+2200	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	UTNEB	IF	N/A	N/A	N/A	+2200	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	IMC	ROMOD	CF	123.25° Mag 100.69° True	N/A	N/A	R2040	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	IMC	MCE03*	CF	123.25° Mag 100.69° True	N/A	N/A	R1557	N/A	N/A	1.50	-3.00	SDF	N/A
40	FINAL	N/A	IMC	RWY12	CF	123.25° Mag 100.69° True	N/A	N/A	@442	N/A	N/A	3.50	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	VA	123.26° Mag 100.69° True	N/A	N/A	+1800	250	-	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	345.00° Mag 322.44° True	L	N/A	N/A	250	-	N/A	N/A	OTHER	N/A
30	MA	N/A	MCE	VAKIK	CF	55.00° Mag 32.25° True	R	N/A	+4000	250	-	N/A	N/A	MAHF	N/A
40	MA	N/A	MCE	VAKIK	HM	55.00° Mag 32.25° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
PUDAL	S 09:40:28.82W 35:52:07.53
UTNEB	S 09:28:39.15W 35:58:08.58
VAKIK	S 09:21:16.15W 35:41:17.40
EKATA	S 09:33:12.71W 35:58:00.00
ROMOD	S 09:29:35.18W 35:53:10.28
RWY12	S 09:30:31.10W 35:48:11.93
MCE03	S 09:29:51.97W 35:51:40.79

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT