



CODING TABLE

VOR Z RWY 28					RIO DE JANEIRO / Galeão - Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_00W		25 FEB 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	SEDBU	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CXI	EPKOG	AF	N/A	R	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	KETUX	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CXI	*CXI26	AF	N/A	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	CXI	EPKOG	CF	263.64° Mag 241.45° True	N/A	N/A	+3500	N/A	N/A	4.08	N/A	IF	N/A
10	FINAL	N/A	N/A	EPKOG	IF	N/A	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	CXI	DETOM	CF	263.67° Mag 241.48° True	N/A	N/A	R1800	N/A	N/A	6.00	N/A	FAF	N/A
30	FINAL	N/A	CXI	*CXI27	CF	263.69° Mag 241.50° True	N/A	N/A	+779	N/A	N/A	3.20	-3.00	SDF	N/A
40	FINAL	N/A	CXI	*CXI28	CF	263.70° Mag 241.51° True	N/A	N/A	@78	N/A	N/A	2.20	-3.00	FTP	N/A
10	MA	N/A	N/A	N/A	VA	264.49° Mag 241.52° True	N/A	N/A	+600	210	-	N/A	N/A	N/A	N/A
20	MA	N/A	N/A	N/A	VI	100.00° Mag 77.03° True	R	N/A	N/A	210	-	N/A	N/A	N/A	N/A
30	MA	N/A	CXI	SEDBU	CF	70.24° Mag 48.05° True	L	N/A	N/A	210	-	N/A	N/A	OTHER	N/A
40	MA	N/A	CXI	EPKOG	AF	N/A	R	N/A	+5000	210	-	N/A	N/A	MAHF	N/A
50	MA	N/A	CXI	EPKOG	HM	263.64° Mag 241.45° True	L	N/A	+5000	210	-	1 min	N/A	MAHF	N/A

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
EPKOG	S 22:42:15.00W 43:02:09.00
DETOM	S 22:45:07.43W 43:07:51.00
CXI27	S 22:46:39.39W 43:10:53.55
CXI28	S 22:47:42.47W 43:12:58.86
SEDBU	S 22:39:32.41W 43:04:12.51
KETUX	S 22:43:20.40W 42:56:51.60
CXI26	S 22:40:04.76W 42:58:24.42

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE