



CODING TABLE

IAC NDB X RWY 30					TABATINGA /Tabatinga, INTL (SBTT)							SBTT_IAC_00E		17 JUN 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	TBT	DARKU	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	TBT	USEDA	AF	N/A	R	N/A	+2500	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	TBT	SUSTU	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	TBT	USEDA	AF	N/A	L	N/A	+2500	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	TBT	USEDA	IF	N/A	N/A	N/A	+2500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	TBT	VULOR	CF	316.80° Mag / 307.40° True	N/A	N/A	R2160	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	TBT	*TBT02	CF	316.77° Mag / 307.37° True	N/A	N/A	@307	N/A	N/A	5.80	-3.00	FTP	N/A
10	MA	N/A	TBT	N/A	CA	317.00° Mag / 307.60° True	N/A	N/A	+1100	240	-	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	120.00° Mag / 110.60 True	L	N/A	+3000	240	-	N/A	N/A	OTHER	N/A
30	MA	N/A	TBT	SUSTU	CF	185.68° Mag / 176.28° True	R	N/A	+3000	240	-	N/A	N/A	MAHF	N/A
40	MA	N/A	TBT	SUSTU	HM	005.68° Mag / 356.28° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	N/A

(*) Fictitious point. Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
TBT	S 04:14:57.60W 69:56:10.20
LET	S 04:11:42.00W 69:56:25.80
VULOR	S 04:18:59.30W 69:50:55.47
*TBT02	S 04:15:26.83W 69:55:32.14
DARKU	S 04:09:34.90W 69:42:34.63
USEDA	S 04:22:02.44W 69:46:56.92
SUSTU	S 04:25:41.94W 69:55:33.85

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT