



CODING TABLE

IAC VOR Z RWY 26					TAUBATÉ / Base de Aviação de Taubaté, MIL (SBTA)							SBTA_IAC_00Q		16 JUN 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	DIDOG	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	TAU	ASETU	AF	N/A	L	N/A	+4900	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	ASETU	IF	N/A	N/A	N/A	+4900	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	TAU	TAU03*	CF	270.55° Mag 248.40° True	N/A	N/A	+3900	N/A	N/A	1.50	N/A	SDF	N/A
30	FINAL	N/A	TAU	NEPER	CF	270.55° Mag 248.41° True	N/A	N/A	R3190	N/A	N/A	1.50	N/A	FAF	N/A
40	FINAL	N/A	TAU	TAU01*	CF	270.55° Mag 248.42° True	N/A	N/A	R2555	N/A	N/A	1.50	-3.99	SDF	N/A
50	FINAL	N/A	TAU	TAU02*	CF	270.55° Mag 248.42° True	N/A	N/A	@1918	N/A	N/A	1.50	-3.99	FTP	N/A
10	MA	N/A	TAU	N/A	CA	270.55° Mag / 248.42° True	N/A	N/A	+3000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	110.00° Mag / 87.89° True	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	MA	N/A	TAU	DIDOG	CF	150.00° Mag / 127.88° True	R	N/A	+6000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	TAU	DIDOG	HM	150.00° Mag / 127.88° True	R	N/A	+6000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purpose

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
TAU	S 23:02:08.55W 45:30:45.13
NEPER	S 23:01:00.06W 45:27:38.09
TAU01	S 23:01:33.29W 45:29:08.81
TAU02	S 23:02:06.51W 45:30:39.54
DIDOG	S 23:05:53.65W 45:25:32.17
ASETU	S 22:59:53.56W 45:24:36.70
TAU03	S 23:00:26.82W 45:26:07.39

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT