



CODING TABLE

IAC RNP W RWY14					FLORIANÓPOLIS / Hercílio Luz, INTL (SBFL)							SBFL_IAC_02K		01 DEC 22	
Seq Num	IAP Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role Of TheFix	Navigation Specification
10	APCH	N/A	N/A	MUKAL	IF	N/A	N/A	N/A	+5100	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	ISASI	TF	141.24° Mag / 121.50° True	N/A	N/A	+2800	N/A	N/A	6.01	N/A	IF	RNP APCH
10	APCH	N/A	N/A	DIMOG	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	ISASI	TF	230.99° Mag / 211.16° True	N/A	N/A	+2800	N/A	N/A	6.03	N/A	IF	RNP APCH
10	APCH	N/A	N/A	ILRUK	IF	N/A	N/A	N/A	+5300	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	ISASI	TF	50.93° Mag / 31.22° True	N/A	N/A	+2800	N/A	N/A	5.97	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	ISASI	IF	N/A	N/A	N/A	+2800	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	IBDOD	TF	140.86° Mag / 121.08° True	N/A	N/A	+2200	N/A	N/A	2.50	N/A	OTHER	RNP APCH
30	FINAL	N	N/A	ESKEG	TF	140.85° Mag / 121.06° True	N/A	N/A	R1980	N/A	N/A	1.50	N/A	FAF	RNP APCH
40	FINAL	N	N/A	FL047*	TF	140.85° Mag / 121.05° True	N/A	N/A	R1280	N/A	N/A	2.19	-3.00	SDF	RNP APCH
50	FINAL	Y	N/A	RWY14	TF	140.84° Mag / 121.04° True	N/A	N/A	@66	N/A	N/A	3.81	-3.00	LTP	RNP APCH
10	MA	N	N/A	FL048	CF	135.45° Mag / 115.62° True	N/A	N/A	N/A	N/A	N/A	7.51	N/A	OTHER	RNP APCH
20	MA	Y	N/A	MATSA	TF	145.27° Mag / 125.40° True	N/A	N/A	+3000	N/A	N/A	9.79	N/A	MAHF	RNP APCH
30	MA	Y	N/A	MATSA	HM	325.30° Mag / 305.40° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

\*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
MUKAL	S 27:31:37.38W 48:48:29.26
ILRUK	S 27:39:53.67W 48:46:11.97
DIMOG	S 27:29:36.03W 48:39:12.38
ISASI	S 27:34:46.34W 48:42:42.99
IBDOD	S 27:36:03.97W 48:40:18.40
ESKEG	S 27:36:50.53W 48:38:51.61
FL047	S 27:37:58.33W 48:36:45.16
RWY14	S 27:39:56.59W 48:33:04.35
FL048	S 27:43:11.84W 48:25:26.42
MATSA	S 27:48:52.80W 48:16:26.40

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT