



## CODING TABLE

IAC VOR Z RWY 12					PRESIDENTE PRUDENTE / Presidente Prudente (SBDN)							SBDN_IAC_00C		23 JAN 25	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	PRR	VUNIX	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	PRR01*	AF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	PRR	ARUKU	CF	117.15° Mag 97.42° True	R	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	PRR	EPGOK	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	PRR02*	AF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	PRR	ARUKU	CF	117.25° Mag 97.52° True	L	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	ARUKU	IF	N/A	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	PRR	EROXU	CF	117.24° Mag 97.45° True	N/A	N/A	R3060	N/A	N/A	6.59	N/A	FAF	N/A
30	FINAL	N/A	N/A	PRR05*	CF	117.27° Mag 97.44° True	N/A	N/A	@1462	N/A	N/A	5.00	-3.00	FTP	N/A
10	MA	N/A	PRR	N/A	CA	117.66° Mag 97.80° True	N/A	N/A	+2600	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	270.00° Mag 250.78° True	R	N/A	+4000	200	-	N/A	N/A	OTHER	N/A
30	MA	N/A	PRR	VUNIX	CF	208.61° Mag 188.44° True	L	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	PRR	VUNIX	HM	28.66° Mag 8.82° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\* Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ARUKU	S 22:08:49.09W 51:38:23.94
EROXU	S 22:09:40.70W 51:31:21.77
VUNIX	S 22:23:34.29W 51:27:47.02
PRR01	S 22:08:38.98W 51:39:47.26
EPGOK	S 22:03:56.39W 51:38:07.51
PRR02	S 22:08:38.84W 51:39:47.24
PRR05	S 22:10:19.80W 51:26:01.30

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT