



## CODING TABLE

IAC ILS Z RWY 04					UBERLÂNDIA / Ten Cel Av César Bombonato (SBUL)							SBUL_IAC_00C		30 DEC 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	UL003	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	UL004	TF	334.12° Mag / 312.63° True	N/A	N/A	+4800	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	UL002	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	UL004	TF	44.17° Mag / 22.73° True	N/A	N/A	+4800	N/A	N/A	5.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	UL001	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	UL004	TF	114.10° Mag / 92.68° True	N/A	N/A	+4800	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	UL004	IF	N/A	N/A	N/A	+4800	N/A	N/A	N/A	N/A	IF	RNAV 1 or RNP 1
20	FINAL	N	IUB	MIMAV	CF	44.20° Mag / 22.74° True	N/A	N/A	+4700	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	Y	IUB	RWY04	CF	44.18° Mag / 22.68° True	N/A	N/A	@3134	N/A	N/A	4.92	-3.00	LTP	N/A
10	MA	Y	N/A	UL008	TF	44.19° Mag / 22.69° True	N/A	N/A	+6000	N/A	N/A	16.13	N/A	MAHF	RNAV 1 or RNP 1
20	MA	Y	N/A	UL008	HM	224.00° Mag / 202.43° True	R	N/A	+6000	N/A	N/A	1.00 min	N/A	MAHF	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
UL001	S19:02:26.40 W 048:24:09.00
UL002	S19:07:21.00 W 048:19:51.60
UL003	S19:06:48.00 W 048:13:09.60
UL004	S19:02:43.20 W 048:17:49.20
MIMAV	S18:58:05.40 W 048:15:46.80
RWY04	S 18 53 32.06 W 048 13 46.94
UL008	S18:38:35.40 W 048:07:13.80
LOC IUB	S18:52:20.05 W 048:13:15.33

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT