



## CODING TABLE

IAC VOR Y RWY 26					BOA VISTA / Atlas Brasil Cantanhede, INTL (SBBV)							SBBV_IAC_00U		31 OCT 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	NENEN	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	BV001*	AF	N/A	R	N/A	+2100	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	BVI	SEKBO	CF	269.92° Mag 253.76° True	N/A	N/A	+2100	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	POSDA	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	BV001*	AF	N/A	L	N/A	+2100	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	BVI	SEKBO	CF	269.92° Mag 253.76° True	N/A	N/A	+2100	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	SEKBO	IF	N/A	N/A	N/A	+2100	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	BVI	UGRON	CF	269.92° Mag 253.76° True	N/A	N/A	R1780	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	BVI	BV103*	CF	269.32° Mag 253.16° True	N/A	N/A	R1080	N/A	N/A	2.41	-3.00	SDF	N/A
40	FINAL	N/A	BVI	BV002*	CF	269.92° Mag 253.76° True	N/A	N/A	@314	N/A	N/A	2.17	-3.00	FTP	N/A
10	MA	N/A	BVI	N/A	CA	269.92° Mag 253.76° True	N/A	N/A	+1500	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	89.00° Mag 72.88° True	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	MA	N/A	BVI	NENEN	CF	50.97° Mag 34.81° True	L	N/A	N/A	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	N/A	NENEN	HM	231.02° Mag 214.81° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\* Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BV002	N 02:51:14.75W 60:40:48.28
SEKBO	N 02:53:56.19W 60:31:37.06
UGRON	N 02:52:31.89W 60:36:24.94
BVI03	N 02:51:51.33W 60:38:43.43
NENEN	N 03:01:01.58W 60:34:21.93
BV001	N 02:54:29.79W 60:29:41.87
POSDA	N 02:46:28.32W 60:30:08.99

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT