



CODING TABLE

IAC ILS Z or LOC Z RWY 06					BELÉM / Val de Cans - Júlio Cezar Ribeiro, INTL (SBBE)							SBBE_IAC_00T		02 DEC 21	
Seq Num	IAP Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role Of TheFix	Navigation Specification
10	APCH	N/A	N/A	SURDI	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	UPORA	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	N/A	BEL09*	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	UPORA	AF	N/A	R	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	UPORA	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	IBE	IBE02*	CF	65.61° Mag / 45.42° True	N/A	N/A	R1690	N/A	N/A	4.57	N/A	FAF	N/A
30	FINAL	N/A	IBE	IBE01*	CF	65.61° Mag / 45.42° True	N/A	N/A	@93	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	VA	65.61° Mag / 45.42° True	N/A	N/A	+1200	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VD	360.00° Mag / 339.81° True	L	N/A	+2000	N/A	N/A	10.00	N/A	OTHER	N/A
30	MA	N/A	N/A	SURDI	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	BEL	SURDI	HM	141.81° Mag / 121.61° True	L	N/A	+2000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purpose

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BEL	S 01:23:03.69W 48:28:42.83
BEL09	S 01:28:19.74W 48:20:12.63
IBE	S 01:22:07.77W 48:27:56.55
IBE01	S 01:23:16.77W 48:29:06.12
IBE02	S 01:26:48.36W 48:32:39.50
SURDI	S 01:17:47.60W 48:37:13.01
UPORA	S 01:30:01.71W 48:35:54.59

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT