



CODING TABLE

SID RNAV PUDPO 1C RWY 27					MANAUS / Ponta Pelada, MIL (SBMN)							SBMN_SID_00Y		03 NOV 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	RWY	N/A	N/A	N/A	CA	272.51° Mag / 256.08° True	N/A	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	RWY	N	N/A	ARSOS	DF	N/A	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
30	RWY	N	N/A	EDNIL	TF	336.63° Mag / 320.33° True	R	-8000	N/A	N/A	N/A	7.81	N/A	OTHER	RNAV 1 or RNP 1
40	RWY	N	N/A	PUDPO	TF	11.23° Mag / 354.94° True	N/A	B9000	B7000	N/A	N/A	11.04	N/A	OTHER	RNAV 1 or RNP 1
10	UKEDA	N/A	N/A	PUDPO	IF	N/A	N/A	B9000	B7000	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	UKEDA	N	N/A	UKEDA	TF	305.40° Mag / 290.36° True	N/A	N/A	N/A	N/A	N/A	143.58	N/A	OTHER	RNAV 1 or RNP 1

DER	Latitude / Longitude (WGS84) DD:MM:SS.SS	Elevation (FT)
27	S 03:08:54.12 W 59:59:44.82	247.70

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ARSOS	S 03:08:19.25W 60:13:43.26
EDNIL	S 03:02:16.77W 60:18:42.28
PUDPO	S 02:51:13.39W 60:19:40.69
UKEDA	S 02:01:07.00W 62:34:12.00

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT