



## CODING TABLE

IAC VOR W RWY 12					ARACAJU / Santa Maria, INTL (SBAR)							SBAR_IAC_00D	18 APR 24		
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	ARU	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	ARU	N/A	FC	309.42° Mag/ 286.67° True	N/A	N/A	+2000	N/A	N/A	12.00	N/A	OTHER	N/A
30	APCH	N/A	ARU	GEDIS	CF	108.27° Mag/ 85.21° True	L	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	GEDIS	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ARU	ESDEP	CF	108.34° Mag/ 85.28° True	N/A	N/A	R1610	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	ARU	ARU01*	CF	107.96° Mag/ 84.91° True	N/A	N/A	R710	N/A	N/A	2.82	-3.00	SDF	N/A
40	FINAL	N/A	ARU	ARU02*	CF	108.18° Mag/ 85.13° True	N/A	N/A	@73	N/A	N/A	2.00	-3.00	FTP	N/A
10	MA	N/A	ARU	N/A	CA	108.18° Mag/ 85.13° True	N/A	N/A	+2000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	ARU	ARU	DF	N/A	R	N/A	+3000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	ARU	ARU	HM	309.42° Mag/ 286.67° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point: Only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR ARU	S 10:58:54.93W 37:04:38.56
GEDIS	S 10:59:45.81W 37:14:46.22
ESDEP	S 10:59:20.43W 37:09:42.48
ARU01	S 10:59:06.07W 37:06:51.17
ARU02	S 10:58:56.78W 37:05:00.52

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT