



## CODING TABLE

IAC ILS W RWY 24					VITÓRIA / Eurico de Aguiar Salles, INTL (SBVT)							SBVT_IAC_01Z		23 MAR 23	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	BIXOG	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	ANGIK	TF	145.74° Mag 121.86° True	N/A	N/A	+2000	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	ESKUK	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	ANGIK	TF	235.71° Mag 211.82° True	N/A	N/A	+2000	N/A	N/A	5.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	CRAVO	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	ANGIK	TF	325.74° Mag 301.85° True	N/A	N/A	+2000	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	ANGIK	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N	IVI	ACNEL	TF	235.72° Mag 211.85° True	N/A	N/A	R1660	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	IVI	RWY24	CF	235.71° Mag 211.85° True	N/A	N/A	@65	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	CA	235.71° Mag 211.85° True	N/A	N/A	+700	210	-	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	MA	Y	N/A	VAPOK	CF	150.00° Mag 126.13° True	L	N/A	N/A	210	-	N/A	N/A	OTHER	RNAV 1 or RNP 1
30	MA	Y	N/A	CRAVO	DF	N/A	L	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	RNAV 1 or RNP 1
40	MA	Y	N/A	CRAVO	HM	325.74° Mag 301.83° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
RWY24	S 20:15:04.00W 40:16:56.33
ESKUK	S 20:02:16.40W 40:08:31.80
ANGIK	S 20:06:32.30W 40:11:19.80
ACNEL	S 20:10:48.10W 40:14:08.00
VAPOK	S 20:20:56.11W 40:15:58.35
BIXOG	S 20:03:21.51W 40:16:44.61
CRAVO	S 20:09:42.92W 40:05:54.77

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT