



CODING TABLE

IAC RNP Z RWY 03					OIAPOQUE / Oiapoque (SBOI)							SBOI_IAC_00E		19 FEB 26	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	OI017	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	OI022	TF	30.37° Mag 11.53° True	N/A	N/A	+2500	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	OI018	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	OI022	TF	100.38° Mag 81.53° True	N/A	N/A	+2500	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	OI019	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	OI022	TF	320.38° Mag 301.53° True	N/A	N/A	+2500	N/A	N/A	5.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	OI022	IF	N/A	N/A	N/A	+2500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	OI021	TF	30.36° Mag 11.53° True	N/A	N/A	+1700	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	OI015*	TF	30.35° Mag 11.53° True	N/A	N/A	R835	N/A	N/A	2.70	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY03	TF	30.35° Mag 11.53° True	N/A	N/A	@103	N/A	N/A	2.30	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	VA	50.00° Mag 31.18° True	N/A	N/A	+1200	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	OI019	DF	N/A	R	N/A	+3000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	OI019	HM	320.24° Mag 301.37° True	R	N/A	+3000	N/A	-	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
OI022	N 03:41:00.52W 51:49:54.56
OI021	N 03:45:55.91W 51:48:54.60
RWY03	N 03:50:51.30W 51:47:54.63
OI017	N 03:36:05.13W 51:50:54.51
OI018	N 03:40:16.09W 51:54:51.36
OI019	N 03:38:22.87W 51:45:38.79
OI015	N 03:48:35.42W 51:48:22.21

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT