



CODING TABLE

IAC VOR RWY 02					BELÉM / Val de Cans - Júlio Cezar Ribeiro, INTL (SBBE)							SBBE_IAC_01A		02 DEC 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	BEL	BEL09*	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	DABEG	AF	N/A	R	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	BEL	SURDI	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BEL	DABEG	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	BEL	DABEG	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	BEL	BEL08*	CF	19.19° Mag / 358.99° True	N/A	N/A	R1550	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	BEL	BEL03*	CF	19.18° Mag / 358.99° True	N/A	N/A	R1060	N/A	N/A	1.52	-3.00	SDF	N/A
40	FINAL	N/A	BEL	BEL06*	CF	19.18° Mag / 358.99° True	N/A	N/A	@71	N/A	N/A	3.11	-3.00	FTP	N/A
10	MA	N/A	N/A	N/A	CA	19.18° Mag / 358.99° True	N/A	N/A	+1200	N/A	N/A	N/A	N/A	N/A	N/A
20	MA	N/A	N/A	N/A	VD	330.00° Mag / 309.82° True	L	N/A	+2000	N/A	N/A	10.00	N/A	N/A	N/A
30	MA	N/A	BEL	SURDI	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	BEL	SURDI	HM	141.81° Mag / 121.61° True	L	N/A	+2000	N/A	N/A	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BEL	S 01:23:03.69W 48:28:42.83
BEL03	S 01:26:33.11W 48:28:39.15
BEL06	S 01:23:25.82W 48:28:42.44
BEL08	S 01:28:05.12W 48:28:37.53
BEL09	S 01:28:19.74W 48:20:12.63
DABEG	S 01:33:06.55W 48:28:32.23
SURDI	S 01:17:47.60W 48:37:13.01

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT