



CODING TABLE

IAC RNAV (GNSS) X RWY 15					FOZ DO IGUAÇU / Cataratas, INTL (SBFI)							SBFI_IAC_00Z		21 APR 22	
Seq Num	IAP Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	ANBAV	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	OPLON	TF	216.83° Mag 200.64° True	N/A	N/A	+3500	N/A	N/A	5.99	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	OPLON	IF	N/A	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	ILMED	TF	147.03° Mag 130.81° True	N/A	N/A	R2370	N/A	N/A	4.65	N/A	FAF	RNP APCH
30	FINAL	N	N/A	FI012*	TF	146.82° Mag 130.59° True	N/A	N/A	R1472	N/A	N/A	2.81	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	FI007	TF	146.82° Mag 130.57° True	N/A	N/A	@767	N/A	N/A	2.21	-3.00	LTP	RNP APCH
10	MA	Y	N/A	FI386	TF	146.92° Mag 130.60° True	N/A	N/A	+3000	N/A	N/A	11.51	N/A	MAHF	RNP APCH
20	MA	Y	N/A	FI386	HM	327.00° Mag 310.60° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

*Fictitious point only for coding purpose

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ANBAV	S 25:23:12.00W 54:35:47.40
OPLON	S 25:28:49.20W 54:38:07.20
ILMED	S 25:31:52.20W 54:34:13.80
FI012	S 25:33:42.36W 54:31:52.06
FI007	S 25:35:09.02W 54:30:00.47
FI386	S 25:42:40.20W 54:20:20.40

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT