



CODING TABLE

IAC VOR X RWY 12					ARACAJU / Santa Maria, INTL (SBAR)							SBAR_IAC_00F		16 MAY 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	ARU	DAKVA	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	GEDIS	AF	N/A	L	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	ARU	ILKUK	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	GEDIS	AF	N/A	R	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	ARU	GEDIS	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ARU	ESDEP	CF	108.19° Mag 85.10° True	N/A	N/A	R1610	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	ARU	ARU08*	CF	108.19° Mag 85.10° True	N/A	N/A	R972	N/A	N/A	2.00	-3.00	SDF	N/A
40	FINAL	N/A	ARU	ARU02*	CF	108.19° Mag 85.10° True	N/A	N/A	@73	N/A	N/A	2.82	-3.00	FTP	N/A
10	MA	N/A	ARU	N/A	CA	108.19° Mag 85.10° True	N/A	N/A	+1500	200	-	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	280.00° Mag 256.96° True	R	N/A	+3000	200	-	N/A	N/A	OTHER	N/A
30	MA	N/A	ARU	ILKUK	CF	236.04° Mag 212.95° True	L	N/A	+3000	200	-	N/A	N/A	MAHF	N/A
40	MA	N/A	ARU	ILKUK	HM	56.04° Mag 32.95° True	R	N/A	+3000	200	-	1.00 min	N/A	MAHF	N/A

*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR ARU	S 10:58:54.93W 37:04:38.56
GEDIS	S 10:59:45.81W 37:14:46.22
ESDEP	S 10:59:20.43W 37:09:42.48
ARU08	S 10:59:10.24W 37:07:40.91
ARU02	S 10:58:55.84W 37:04:49.40
ILKUK	S 11:07:20.40W 37:10:10.80
DAKVA	S 10:51:20.00W 36:57:58.30

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT