



## CODING TABLE

IAC ILS Z or LOC Z RWY 35					CUJIABÁ/ Marechal Rondon, INTL (SBCY)							SBCY_IAC_00K		26 DEC 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	UBDON	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CIA	CIA03*	AF	N/A	R	N/A	+2600	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	ICB	UDUNU	CF	351.32° Mag 332.75° True	N/A	N/A	+2600	N/A	N/A	1.54	N/A	IF	N/A
10	APCH	N/A	N/A	LIXAP	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CIA	CIA04*	AF	N/A	L	N/A	+2600	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	ICB	UDUNU	CF	351.32° Mag 332.75° True	N/A	N/A	+2600	N/A	N/A	1.69	N/A	IF	N/A
10	FINAL	N/A	N/A	UDUNU	IF	N/A	N/A	N/A	+2600	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ICB	XODUP	CF	351.32° Mag 332.75° True	N/A	N/A	R2230	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	Y	ICB	RWY35	CF	351.32° Mag 332.75° True	N/A	N/A	@641	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	VA	351.32° Mag 332.75° True	N/A	N/A	+1700	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	CIA	ANLED	CF	359.37° Mag 340.79° True	R	N/A	+4000	230	-	N/A	N/A	MAHF	N/A
30	MA	N/A	CIA	ANLED	HM	179.37° Mag 160.79° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
UDUNU	S 15:48:39.57W 56:01:57.35
XODUP	S 15:44:11.79W 56:04:19.89
ANLED	S 15:25:08.42W 56:11:49.91
UBDON	S 15:45:53.82W 55:56:25.56
CIA03	S 15:50:01.98W 56:01:13.59
LIXAP	S 15:51:25.18W 56:07:29.30
CIA04	S 15:50:10.28W 56:01:09.17
RWY35	S 15:39:43.99W 56:06:42.33

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT