



## CODING TABLE

IAC VOR X RWY 02C					PIRASSUNUNGA / Campo Fontenelle, MIL (SBYS)							SBYS_IAC_00S		08 AUG 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	PIR	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	PIR	PIR	FC	206.78° Mag 184.94° True	N/A	N/A	+3700	N/A	N/A	7.00	N/A	OTHER	N/A
30	APCH	N/A	PIR	KIDOK	CF	13.71° Mag 351.87° True	L	N/A	R3430	N/A	N/A	N/A	N/A	FAF	N/A
10	FINAL	N/A	PIR	KIDOK	IF	N/A	N/A	N/A	R3430	N/A	N/A	N/A	N/A	FAF	N/A
20	FINAL	N/A	PIR	YS027*	CF	13.71° Mag 351.87° True	N/A	N/A	@2018	N/A	N/A	5.00	-3.00	FTP	N/A
10	MA	N/A	PIR	PIR	CA	13.50° Mag 351.66° True	N/A	N/A	+4000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	DF	N/A	L	N/A	+5000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	PIR	PIR	HM	206.84° Mag 185.00° True	R	N/A	+5000	N/A	N/A	1.00 min	N/A	MAHF	N/A

\*Fictitious point only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VOR PIR	S 21:59:04.42W 47:20:40.21
KIDOK	S 22:04:02.56W 47:19:54.52
YS027	S 21:59:39.11W 47:20:34.90

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT