



## CODING TABLE

IAC RNP RWY 27					POÇOS DE CALDAS / Embaixador Walther Moreira Salles (SBPC)							SBPC_IAC_00H		16 JUN 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	PC007	IF	N/A	N/A	N/A	+8000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	PC006	TF	181.68° Mag / 159.73° True	N/A	N/A	+6500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	PC008	IF	N/A	N/A	N/A	+8000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	PC006	TF	271.68° Mag / 249.69° True	N/A	N/A	+6500	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	PC009	IF	N/A	N/A	N/A	+8000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	PC006	TF	1.66° Mag / 339.71° True	N/A	N/A	+6500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	PC006	IF	N/A	N/A	N/A	+6500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	PC004	TF	271.67° Mag / 249.72° True	N/A	N/A	R5780	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	PCL04*	TF	271.70° Mag / 249.78° True	N/A	N/A	R5154	N/A	N/A	1.96	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY27	TF	271.69° Mag / 249.80° True	N/A	N/A	@4186	N/A	N/A	3.04	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	271.69° Mag / 249.81° True	N/A	N/A	+5500	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	PC009	DF	N/A	L	N/A	+8000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	PC009	HM	1.66° Mag / 339.71° True	R	N/A	+8000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

\*Fictitious point only for coding purposes

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
PC009	S 21:52:34.94W 46:21:26.40
PC006	S 21:46:56.07W 46:23:40.55
PC004	S 21:48:40.34W 46:28:42.97
PCL04	S 21:49:21.12W 46:30:41.60
PC007	S 21:41:17.17W 46:25:54.53
RWY27	S 21:50:24.30 W 46:33:45.57
PC008	S 21:45:11.65W 46:18:38.25

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT