



CODING TABLE

IAC VOR Y RWY 30					PRESIDENTE PRUDENTE / Presidente Prudente (SBDN)							SBDN_IAC_00D		29 DEC 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	PRR	VUNIX	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	PRR03*	AF	N/A	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	PRR	UGOLI	CF	299.33° Mag 279.39° True	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	PRR	ORUDI	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	PRR04*	AF	N/A	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	PRR	UGOLI	CF	299.33° Mag 279.39° True	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	APCH	N/A	PRR	SEDPI	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	PRR06*	AF	N/A	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	PRR	UGOLI	CF	299.33° Mag 279.39° True	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	UGOLI	IF	N/A	N/A	N/A	+3500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	PRR	ENVAP	CF	299.41° Mag 279.53° True	N/A	N/A	R3130	N/A	N/A	6.32	N/A	FAF	N/A
30	FINAL	N/A	PRR	PRR07*	CF	299.39° Mag 279.55° True	N/A	N/A	@1531	N/A	N/A	5.00	-3.00	FTP	N/A
10	MA	N/A	PRR	N/A	CA	299.40° Mag 279.59° True	N/A	N/A	+2600	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	N/A	N/A	VI	165.00° Mag 145.92° True	L	N/A	+4000	200	-	N/A	N/A	OTHER	N/A
30	MA	N/A	PRR	VUNIX	CF	208.61° Mag 188.84° True	R	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	N/A
40	MA	N/A	PRR	VUNIX	HM	28.66° Mag 8.82° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	N/A

* Fictitious point for coding purposes only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
UGOLI	S 22:12:22.61W 51:12:49.74
ENVAP	S 22:11:19.68W 51:19:33.02
VUNIX	S 22:23:34.29W 51:27:47.02
PRR03	S 22:12:34.29W 51:11:26.61
ORUDI	S 22:16:58.94W 51:13:08.34
PRR04	S 22:12:34.14W 51:11:27.56
SEDPI	S 22:07:39.24W 51:11:39.49
PRR06	S 22:12:37.08W 51:11:33.16
PRR07	S 22:10:29.77W 51:24:51.78

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT