



CODING TABLE

IAC RNP Y RWY 26					BOA VISTA / Atlas Brasil Cantanhede, INTL (SBBV)							SBBV_IAC_000		08 AUG 24	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	BV013	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	BV009	TF	329.29° Mag 313.02° True	N/A	N/A	+2500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	BV011	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	BV009	TF	189.23° Mag 173.02° True	N/A	N/A	+2500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	BV012	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	BV009	TF	259.29° Mag 243.02° True	N/A	N/A	+2500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	BV009	IF	N/A	N/A	N/A	+2500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	BV008	TF	259.25° Mag 243.02° True	N/A	N/A	R1910	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	BV014*	TF	259.22° Mag 243.02° True	N/A	N/A	+1020	N/A	N/A	2.84	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY26	TF	259.19° Mag 243.01° True	N/A	N/A	@314	N/A	N/A	2.16	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	259.17° Mag 243.01° True	N/A	N/A	+1500	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	BV011	DF	N/A	R	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	BV011	HM	188.66° Mag 173.02° True	R	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

* Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
BV013	N 02:51:33.58W 60:27:27.70
BV009	N 02:55:40.41W 60:31:50.75
BV011	N 03:01:39.49W 60:32:34.49
BV008	N 02:53:23.62W 60:36:17.96
BV014	N 02:52:05.92W 60:38:49.74
RWY26	N 02:51:06.82W 60:40:45.15
BV012	N 02:58:24.52W 60:26:30.08

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT