



## CODING TABLE

IAC RNP Y RWY 06					VITÓRIA / Eurico de Aguiar Salles, INTL (SBVT)							SBVT_IAC_00S		23 MAR 23	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	VT032	IF	N/A	N/A	N/A	+4500	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VT017	TF	145.69° Mag 121.86° True	N/A	N/A	+2500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VT014	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VT017	TF	55.72° Mag 31.88° True	N/A	N/A	+2500	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	VT012	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	VT017	TF	325.69° Mag 301.86° True	N/A	N/A	+2500	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	VT017	IF	N/A	N/A	N/A	+2500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	VT018	TF	55.71° Mag 31.86° True	N/A	N/A	R2040	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	VRI20*	TF	55.72° Mag 31.87° True	N/A	N/A	R1406	N/A	N/A	1.60	-3.72	SDF	RNP APCH
40	FINAL	N	N/A	VRI21*	TF	55.72° Mag 31.87° True	N/A	N/A	R1134	N/A	N/A	0.69	-3.72	SDF	RNP APCH
50	FINAL	Y	N/A	RWY06	TF	55.72° Mag 31.86° True	N/A	N/A	@63	N/A	N/A	2.71	-3.72	LTP	RNP APCH
10	MA	N/A	N/A	N/A	VA	55.74° Mag 31.87° True	N/A	N/A	+1300	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	VT012	DF	N/A	R	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	VT012	HM	325.72° Mag 301.86° True	L	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

\* Fictitious point: only for coding purposes.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
VT017	S 20:24:23.70W 40:23:05.20
VT018	S 20:20:08.00W 40:20:16.60
VRI20	S 20:18:46.17W 40:19:22.67
VRI21	S 20:18:10.96W 40:18:59.46
RWY06	S 20:15:52.34W 40:17:28.16
VT032	S 20:21:12.91W 40:28:30.63
VT014	S 20:28:39.40W 40:25:54.00
VT012	S 20:27:34.32W 40:17:39.55

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE