



## CODING TABLE

IAC ILS Y RWY 24R					ANÁPOLIS / Campo Marechal Márcio de Souza e Mello, MIL (SBAN)							SBAN_IAC_00Z	20 MAR 25		
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	AN008	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	AN011	TF	240.70° Mag 219.08° True	N/A	N/A	+5300	N/A	N/A	5.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	AN007	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	AN011	TF	310.73° Mag 289.11° True	N/A	N/A	+5300	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	AN009	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	AN011	TF	170.73° Mag 149.11° True	N/A	N/A	+5300	N/A	N/A	6.00	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	AN011	IF	N/A	N/A	N/A	+5300	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	IAN	GUXIT	CF	240.77° Mag 219.17° True	N/A	N/A	R5230	N/A	N/A	4.50	N/A	FAF	N/A
30	FINAL	N/A	IAN	RW24R	CF	240.62° Mag 219.04° True	N/A	N/A	@3706	N/A	N/A	5.50	-2.60	LTP	N/A
10	MA	Y	N/A	AN002	TF	240.70° Mag 219.04° True	N/A	N/A	+7000	N/A	N/A	N/A	N/A	MAHF	RNAV 1 or RNP 1
20	MA	Y	N/A	AN002	HM	60.68° Mag 39.09° True	R	N/A	+7000	N/A	N/A	1.00 min	N/A	MAHF	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
AN011	S 16:05:07.50 W 48:50:40.60
GUXIT	S 16:08:37.89 W 48:53:37.49
RW24R	S 16:12:55.10 W 48:57:13.69
AN008	S 16:01:13.60 W 48:47:24.20
AN007	S 16:07:05.80 W 48:44:47.20
AN009	S 15:59:57.30 W 48:53:52.40
AN002	S 16:25:59.50 W 49:08:14.40

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT