



## CODING TABLE

IAC RNP RWY 17					GUAJARÁ-MIRIM / Guajará-Mirim (SBGM)							SBGM_IAC_001		01 DEC 22	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	GM006	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	GM004	TF	248.05° Mag 236.44° True	N/A	N/A	+2100	N/A	N/A	5.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	GM007	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	GM004	TF	178.05° Mag 166.44° True	N/A	N/A	+2100	N/A	N/A	5.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	GM004	IF	N/A	N/A	N/A	+2100	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	ANDUB	TF	178.05° Mag 166.44° True	N/A	N/A	+2100	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	GM013*	TF	178.05° Mag 166.44° True	N/A	N/A	+1200	N/A	N/A	2.84	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY17	TF	178.05° Mag 166.44° True	N/A	N/A	@504	N/A	N/A	2.20	-3.00	LTP	RNP APCH
10	MA	N/A	N/A	N/A	CA	178.05° Mag 166.44° True	N/A	N/A	+2500	N/A	N/A	N/A	N/A	OTHER	RNP APCH
20	MA	Y	N/A	GM006	DF	N/A	L	N/A	+3000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	GM006	HM	248.05° Mag 236.44° True	L	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

\* Fictitious Point: Only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
GM007	S 10:32:03.52W 65:20:46.75
GM004	S 10:36:56.50W 65:19:35.34
ANDUB	S 10:41:49.48W 65:18:23.91
GM013	S 10:44:33.54W 65:17:43.88
RWY17	S 10:46:42.45W 65:17:12.43
GM006	S 10:34:09.87W 65:15:21.52

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT